

Specifiche tecniche Digital Designs serie VO

B1 BULLET TWEETER (5kHz 12 dB/oct crossover incluso)

Frequency Response	4kHz – 22kHz
Power handling RMS / Program	50 / 100 Watts
Voice Coil Diameter	1" / 25mm
Diaphragm Material	Titanium
Sensitivity	103 dB
Impedance	4 Ohm

B2 BULLET TWEETER (5kHz 12 dB/oct crossover incluso)

Frequency Response	3.5kHz – 20kHz
Power Handling RMS / Program	75 / 150 Watts
Voice Coil Diameter	1.6" / 40mm
Diaphragm Material	Titanium
Sensitivity	108 dB
Impedance	4 Ohm

M – 6.5 165mm MIDRANGE (HybridZ motor with Faraday Ring)

Frequency Response	100 Hz – 16kHz
Power Handling RMS / Program	150 / 300 Watts
Voice Coil Diameter	1.5" / 38mm
Cone Material	Synthetic Blend
Sensitivity	98 dB
Impedance	4 Ohm

M – 8.0 200mm MIDRANGE (HybridZ motor with Faraday Ring)

Frequency Response	100 Hz – 13Khz
Power Handling	150 / 300 Watts
Voice Coil Diameter	1.5" / 38mm
Cone Material	Synthetic Blend
Sensitivity	100 dB
Impedance	4 Ohm